



Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity 150

26W Unity 150 4000K LED Wallwash

Code: AULED150WW



PRODUCT FEATURES

- Recessed adjustable architectural wallwash with 355° rotation suitable for commercial, hospitality and retail applications
- 30° cut-off angle in the horizontal position
- Remote driver with plug and play connection
- Powered by Tridonic
- Adjustable tilt angle from -15° to 45°
- Die-cast aluminium body and heatsink for good thermal management
- Dimmable options

GENERAL INFORMATION

Wattage	28
Lumens Delivered	2700lm
Lm/W	93lm/W
Beam Angle	55
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	16
Cut-Out Size	150
Energy efficiency class	E
Product Weight without Packaging	0.766 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP20
IK Rating	IK02
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	162 mm
Height	138 mm



Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity 150

26W Unity 150 4000K LED Wallwash

Code: AULED150WW

