













Unity S and R s

Unity Rectangular 2 Downlight DALI Code: AULED2/REC/DD3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality,
	Residential, Retail
Specification	Architectural





- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Black trim provides excellent glare control

www.ansell-lighting.com

- Remote driver with plug and play connection
- · Powered by Tridonic

- Fully adjustable tilt angle 30° on two axis
- Steel housing with die-cast aluminium body for good thermal management
- · Dimmable options

GENERAL INFORMATION			
Wattage	2 x 37W		
Lumens Delivered	2 x 3100lm		
Lm/W	88lm/W		
Beam Angle	40		
CRI	90		
CCT	4000K		
Input	220-240V		
Operating Temp	-20°C - 25°C		
SDCM	3		
UGR	13		
Cut-Out Size	325x152mm		
Product Weight without Packag	ing 2.41 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	152 mm	

