




Unity S and R s

Unity Rectangular 2 Downlight 1-10V Emergency
Code: AULED2/REC/DD4/M3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Black trim provides excellent glare control
- Remote driver with plug and play connection
- Powered by Tridonic
- Fully adjustable tilt angle 30° on two axis
- Steel housing with die-cast aluminium body for good thermal management
- Dimmable options

GENERAL INFORMATION	
Wattage	2 x 37W
Lumens Delivered	2 x 3100lm
Lm/W	88lm/W
Beam Angle	40
CRI	90
CCT	4000K
Input	220/240V
Operating Temp	0°C - 25°C
SDCM	3
UGR	13
Cut-Out Size	325x152mm
Product Weight without Packaging	0.01 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Height	152 mm

