





Unity S and R s

Unity Rectangular 2 Downlight 1-10V Code: AULED2/REC/DD4

Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	





- Fully adjustable tilt angle 30° on two axis
- Steel housing with die-cast aluminium body for good thermal management
- Dimmable options
- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Black trim provides excellent glare control
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION		
2 x 37W		
2 x 3100lm		
88lm/W		
40		
90		
4000K		
220-240V		
-20°C - 25°C		
3		
13		
325x152mm		
0.01 kg		
	2 x 37W 2 x 3100lm 88lm/W 40 90 4000K 220-240V -20°C - 25°C 3 13 13 325x152mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	152 mm	

