













## Unity S and R Retractable s

Unity Rectangular Retractable Downlight DALI **Code:** AULED2/RMP/DD3/M3

Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	







- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Retractable head design allows for a range of installation applications
- Steel housing with die-cast aluminium body for excellent thermal management
- · Dimmable options

- Full 360° head rotation and 90° tilting capability
- Black trim provides excellent glare control
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION		
Wattage	2 x15W	
Lumens Delivered	2 x 1000lm	
Lm/W	73lm/W	
Beam Angle	50	
CRI	90	
ССТ	4000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	5	
UGR	14	
Cut-Out Size	158x90mm	
Product Weight without Packaging	0.01 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	106 mm	

**www.ansell-lighting.com** Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

