






Unity 80

Unity 80 Downlight Warm White DSI
Code: AULED80D/WW/DD2

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |



- IP44 (downlight only) compact high performance architectural downlight and gimbal suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Powered by Tridonic
- 30° tilt angle (gimbal only)
- Mirror finished anodized reflector
- Remote driver with plug and play connection

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 15W |
| Lumens Delivered | 800lm |
| Lm/W | 55lm/W |
| Beam Angle | 55 |
| CRI | 90 |
| CCT | 3000K |
| Input | 220-240V |
| Operating Temp | -20°C - 25°C |
| SDCM | 5 |
| UGR | 19 |
| Cut-Out Size | 80mm |
| Product Weight without Packaging | 0.01 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L70 50,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 90 mm |
| Height | 83 mm |

