




Unity 80 Gimbal

Unity 80 Gimbal Warm White 1-10V Self-Test
Code: AULED80GIM/WW/DD4/SM3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- IP44 (downlight only) compact high performance architectural downlight and gimbal suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Powered by Tridonic
- 30° tilt angle (gimbal only)
- Mirror finished anodized reflector
- Remote driver with plug and play connection

GENERAL INFORMATION	
Wattage	15W
Lumens Delivered	800lm
Lm/W	55lm/W
Beam Angle	55
CRI	90
CCT	3000K
Input	220/240V
Operating Temp	0°C - 25°C
SDCM	3
UGR	19
Cut-Out Size	80mm

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	90 mm
Height	73 mm

