




<b>Category</b>	Downlights
<b>Application</b>	Ancillary, Commercial, Education, Hospitality, Residential, Retail
<b>Specification</b>	Architectural

# Unity 80 Gimbal

13W Unity 80 3000K LED Gimbal

**Code:** AULED80GIM/WW



## PRODUCT FEATURES

- IP44 (downlight only) compact high performance architectural downlight and gimbal suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Powered by Tridonic
- 30° tilt angle (gimbal only)
- Mirror finished anodized reflector
- Remote driver with plug and play connection

### GENERAL INFORMATION

<b>Wattage</b>	15
<b>Lumens Delivered</b>	800lm
<b>Lm/W</b>	55lm/W
<b>Beam Angle</b>	55
<b>CRI</b>	90
<b>CCT</b>	3000K
<b>Input</b>	220-240V
<b>Operating Temp</b>	-20°C - 25°C
<b>SDCM</b>	3
<b>UGR</b>	19
<b>Cut-Out Size</b>	80
<b>Energy efficiency class</b>	E
<b>Product Weight without Packaging</b>	0.306 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP20
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Recessed
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Diameter</b>	90 mm
<b>Height</b>	73 mm





<b>Category</b>	Downlights
<b>Application</b>	Ancillary, Commercial, Education, Hospitality, Residential, Retail
<b>Specification</b>	Architectural

# Unity 80 Gimbal

13W Unity 80 3000K LED Gimbal  
Code: AULED80GIM/WW

