




| | |
|----------------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity 80 Gimbal

13W Unity 80 4000K LED Gimbal

Code: AULED80GIM



PRODUCT FEATURES

- IP44 (downlight only) compact high performance architectural downlight and gimbal suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Powered by Tridonic
- 30° tilt angle (gimbal only)
- Mirror finished anodized reflector
- Remote driver with plug and play connection

GENERAL INFORMATION

| | |
|----------------------------------|--------------|
| Wattage | 15 |
| Lumens Delivered | 1200lm |
| Lm/W | 80lm/W |
| Beam Angle | 55 |
| CRI | 90 |
| CCT | 3000K |
| Input | 220-240V |
| Operating Temp | -20°C - 25°C |
| SDCM | 3 |
| UGR | 18 |
| Cut-Out Size | 80 |
| Energy efficiency class | E |
| Product Weight without Packaging | 0.315 kg |

TECHNICAL INFORMATION

| | |
|--------------------------------|----------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 90 mm |
| Height | 73 mm |





| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity 80 Gimbal

13W Unity 80 4000K LED Gimbal
Code: AULED80GIM

