




Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White
Code: AULEDGCP/CW/DD3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector for optimum light control
- Triac dimmable as standard
- Deep cut-off angle for glare control and comfort
- 30° tilt angle
- Remote driver with plug and play connection
- Powered by HEP

GENERAL INFORMATION	
Wattage	12W
Lumens Delivered	400lm
Lm/W	34lm/W
Beam Angle	30
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	10
Cut-Out Size	75mm
Product Weight without Packaging	0.376 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	Matt White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	88 mm
Height	113 mm

