













Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White Code: AULEDGCP/CW/OCTO

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality,
	Residential, Retail
Specification	Architectural





- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated and $30^{\circ}\,\text{cut-off}$ angle
- Mirror finished anodized reflector for optimum light control
- Triac dimmable as standard

- · Deep cut-off angle for glare control and comfort
- 30° tilt angle
- Remote driver with plug and play connection
- Powered by HEP

GENERAL INFORMATION			
Wattage	12W		
Lumens Delivered	400lm		
Lm/W	34lm/W		
Beam Angle	30		
CRI	90		
CCT	4000K		
Input	220-240V		
Operating Temp	-20°C - 25°C		
SDCM	3		
UGR	10		
Cut-Out Size	75mm		
Product Weight without Packaging	0.54 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Matt White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	88 mm	
Height	113 mm	