



Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White

Code: AULEDGCP/CW

PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector for optimum light control
- Triac dimmable as standard
- Deep cut-off angle for glare control and comfort
- 30° tilt angle
- Remote driver with plug and play connection
- Powered by HEP

GENERAL INFORMATION

Wattage	12W
Lumens Delivered	400lm
Lm/W	34lm/W
Beam Angle	30
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	10
Cut-Out Size	75mm
Product Weight without Packaging	0.376 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Matt White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	88 mm
Height	113 mm





Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White
Code: AULEDGCP/CW

