



| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White

Code: AULEDGCP/CW

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector for optimum light control
- Triac dimmable as standard
- Deep cut-off angle for glare control and comfort
- 30° tilt angle
- Remote driver with plug and play connection
- Powered by HEP

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 12W |
| Lumens Delivered | 400lm |
| Lm/W | 34lm/W |
| Beam Angle | 30 |
| CRI | 90 |
| CCT | 4000K |
| Input | 220-240V |
| Operating Temp | -20°C - 25°C |
| SDCM | 3 |
| UGR | 10 |
| Cut-Out Size | 75mm |
| Product Weight without Packaging | 0.376 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | Matt White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L70 50,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 88 mm |
| Height | 113 mm |





| | |
|----------------------|---|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity GC Pro Adjustable

Unity GC Pro Adjustable Downlight Cool White

Code: AULEDGCP/CW

