Unity Downlight

Part of the Downlights product category

Model	Unity GC Pro Adjustable Downlight Cool White
Code	AULEDGCP/CW
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	12W
Operating Temp	-20°C - 25°C
Lumens Delivered	400lm
lm/W	34lm/W
CCT	4000K
UGR	10
Beam Angle	30

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	N/A
Product Weight without Packaging	0.376 kg
Colour / Finish	Matt White
Diameter	88 mm
Height	113 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.8985
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Deep cut-off angle for glare control and comfort
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- 30° tilt angle
- Mirror finished anodized reflector for optimum light control

Unity Downlight

Part of the Downlights product category

Model	Unity GC Pro Adjustable Downlight Cool White
Code	AULEDGCP/CW
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail



