


Unity GC Pro Fixed

Unity GC Pro 1 Fixed Downlight Cool White DSI Code: AULEDGCP1/CW/DD4

	- S e	N G
@ansell_lighting	f	anselllighting
Ansell Lighting	0	ansell_lighting

Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	





- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection

- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control
- Powered by HEP

GENERAL INFORMATION		
Wattage	3W	
Lumens Delivered	120lm	
Lm/W	40lm/W	
Beam Angle	30	
CRI	90	
CCT	4000K	
Input	220-240V	
Operating Temp	-20°C - 25°C	
SDCM	3	
UGR	10	
Cut-Out Size	40mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Matt White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 82,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	48 mm	
Height	48 mm	