# Unity Downlight

Part of the Downlights product category

| | |
|---|---|
| **Model** | Unity GC Pro 1 Fixed Downlight Cool White |
| **Code** | AULEDGCP1/CW |
| **Application** | Ancillary, Commercial, Education, Hospitality, Residential, Retail |



## GENERAL INFORMATION

| | |
|---|---|
| **Input** | 220-240V |
| **Wattage** | 3W |
| **Operating Temp** | -20°C - 25°C |
| **Lumens Delivered** | 140lm |
| **lm/W** | 47lm/W |
| **CCT** | 4000K |
| **UGR** | 10 |
| **Beam Angle** | 30 |

## MATERIAL INFORMATION

| | |
|---|---|
| **Main Material** | Aluminium |
| **Diffuser Material** | \|N/A\| |
| **Product Weight without Packaging** | 0.083 kg |
| **Colour / Finish** | Matt White |
| **Diameter** | 48 mm |
| **Height** | 48 mm |

## TECHNICAL INFORMATION

| | |
|---|---|
| **Class Protection** | 2 |
| **Light Source** | LED |
| **SDCM (Initial Macadam)** | 3 |
| **CRI** | 90 |
| **Internal / External** | Internal |
| **Surface / Recessed / Suspended** | Recessed |
| **Power Factor** | 0.451 |
| **L70 @ 25°C** | L70 B50 82,000h |

## PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Deep cut-off angle for glare control and comfort
- Die-cast aluminium construction, powder coated
- Mirror finished anodized reflector for optimum light control
- Remote driver with plug and play connection

## ACCESSORIES

| | |
|---|---|
| ACFLP/3 | LED Emergency Lighting Pack Maintained / Non-Maintained |

# Unity Downlight

Part of the Downlights product category

| | |
|---|---|
| **Model** | Unity GC Pro 1 Fixed Downlight Cool White |
| **Code** | AULEDGCP1/CW |
| **Application** | Ancillary, Commercial, Education, Hospitality, Residential, Retail |




