



Unity Downlight

Part of the Downlights product category



Model Unity GC Pro 1 Fixed Downlight Cool White
Code AULEDGCP1/CW
Application Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

| | |
|-------------------------|--------------|
| Input | 220-240V |
| Wattage | 3W |
| Operating Temp | -20°C - 25°C |
| Lumens Delivered | 140lm |
| lm/W | 47lm/W |
| CCT | 4000K |
| UGR | 10 |
| Beam Angle | 30 |

MATERIAL INFORMATION

| | |
|---|------------|
| Main Material | Aluminium |
| Diffuser Material | N/A |
| Product Weight without Packaging | 0.083 kg |
| Colour / Finish | Matt White |
| Diameter | 48 mm |
| Height | 48 mm |

TECHNICAL INFORMATION

| | |
|---------------------------------------|-----------------|
| Class Protection | 2 |
| Light Source | LED |
| SDCM (Initial Macadam) | 3 |
| CRI | 90 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Power Factor | 0.451 |
| L70 @ 25°C | L70 B50 82,000h |

PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Deep cut-off angle for glare control and comfort
- Die-cast aluminium construction, powder coated
- Mirror finished anodized reflector for optimum light control
- Remote driver with plug and play connection

ACCESSORIES

| | |
|---------|---|
| ACFLP/3 | LED Emergency Lighting Pack Maintained / Non-Maintained |
|---------|---|





Unity Downlight

Part of the Downlights product category



Model Unity GC Pro 1 Fixed Downlight Cool White
Code AULEDGCP1/CW
Application Ancillary, Commercial, Education, Hospitality, Residential, Retail

