



Downlights
Ancillary, Commercial, Education, Hospitality,
Residential, Retail
Architectural

Unity GC Pro Fixed

Unity GC Pro 2 Fixed Downlight Cool White Code: AULEDGCP2/CW

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection

- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control
- Powered by HEP

GENERAL INFORMATION				
Wattage	7W			
Lumens Delivered	310lm			
Lm/W	45lm/W			
Beam Angle	30			
CRI	90			
CCT	4000K			
Input	220-240V			
Operating Temp	-20°C - 25°C			
SDCM	3			
UGR	10			
Cut-Out Size	55mm			
Product Weight without Packaging	0.135 kg			

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	Matt White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 82,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	65 mm
Height	70 mm
Accessories	ACFLP/3

Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333













Category	Downlights			
Application	Ancillary, Commercial, Education, Hospitality,			
	Residential, Retail			
Specification	Architectural			

Unity GC Pro Fixed

Unity GC Pro 2 Fixed Downlight Cool White Code: AULEDGCP2/CW





17.70	A A	ESS(la La	
141	BE 88	-	1174	134

ACFLP/3

LED Emergency Lighting Pack Maintained / Non-Maintained

Warrington: +44 (0) 1942 433333





