


Unity GC Pro Fixed

Unity GC Pro 3 Fixed Downlight Warm White Code: AULEDGCP3/WW

	36	N G
@ansell_lighting	f	anselllighting
Ansell Lighting	Ø	ansell_lighting

Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	



PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection

- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control
- Powered by HEP

GENERAL INFORMATION		
Wattage	14W	
Lumens Delivered	720lm	
Lm/W	53lm/W	
Beam Angle	30	
CRI	90	
CCT	3000K	
Input	220/240V	
Operating Temp	-20°C - 25°C	
SDCM	3	
UGR	10	
Cut-Out Size	68mm	
Product Weight without Packag	ing 0.248 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Matt White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 82,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	78 mm	
Height	81 mm	