



Unity Wallwash

Part of the Downlights product category



Model	Unity 1 Wallwash Cool White
Code	AUNW1/1/CW
Application	Commercial, Education, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	10W
Operating Temp	-20°C - 25°C
Lumens Delivered	1200lm
lm/W	120lm/W
CCT	4000K
UGR	20
Beam Angle	50

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without	0.57 kg
Packaging	
Colour / Finish	Sand White
Diameter	110 mm
Height	79 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.97
L70 @ 25°C	L70 100,000h

PRODUCT FEATURES

- Retractable head recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Upto 130lm/W efficiency and CRI 90 provides elite level performance and light quality
- Extension, tilting and rotation within one product
- Adjustable tilt angle from -15° to 30°
- Die-cast aluminium body and heatsink for good thermal management





Unity Wallwash

Part of the Downlights product category



Model	Unity 1 Wallwash Cool White
Code	AUNW1/1/CW
Application	Commercial, Education, Hospitality, Retail

