



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage

Vantage CCT 1 Downlight
Code: AVAN1/1



PRODUCT FEATURES

- Performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Downlight design allows installation into existing hole cut-outs from 68mm, 100mm, 150mm and 200mm
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire

GENERAL INFORMATION

Wattage	6.5W - 8W
Lumens Delivered	650lm - 880lm (4000K)
Lm/W	105lm/W
Beam Angle	80
CRI	80
CCT	3000K-4000K-6500K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	24
Cut-Out Size	68
Product Weight without Packaging	0.18 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 100,000
Warranty (Years)	5
CE Mark	Yes
Diameter	82 mm
Height	54 mm





Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage

Vantage CCT 1 Downlight
Code: AVAN1/1

