



Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage

Vantage CCT 3 Downlight





PRODUCT FEATURES

- Performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire

G	ENERAL INFORMATION
Wattage	15W - 18W
Lumens Delivered	1900lm - 2300lm (4000K)
Lm/W	125lm/W
Beam Angle	80
CRI	80
CCT	3000K-4000K-6500K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	24
Cut-Out Size	150
Product Weight without Packaging	0.32 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 100,000	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	172 mm	
Height	98 mm	











Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Vantage

Vantage CCT 3 Downlight Code: AVAN3/1







