





Downlights

Hospitality, Retail

Performance

@ansell\_lighting





in Ansell Lighting




## Vantage

## Vantage CCT 1 Downlight Switch Dim Self-Test Code: AVANTLED1/DD1/SM3



www.ansell-lighting.com





Category

**Application** 

Specification



Ancillary, Commercial, Education, Healthcare,

## PRODUCT FEATURES

- CCT selectable LED performance downlight suitable for commercial and education applications
- One product provides 3000K,4000K and 6500K colour temperature options
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

GENERAL INFORMATION		
Wattage	8.5W	
Lumens Delivered	740lm (4000K)	
Lm/W	107lm/W (4000K)	
Beam Angle	75	
CRI	80	
CCT	3000/4000/6500K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	6	
UGR	27	
Cut-Out Size	68mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	82 mm	
Height	54 mm	