












## Vantage


## Vantage CCT 2 Downlight 1-10V Emergency Code: AVANTLED2/DD4/M3











- CCT selectable LED performance downlight suitable for commercial and education applications
- One product provides 3000K,4000K and 6500K colour temperature options
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

GENERAL INFORMATION		
Wattage	14W	
Lumens Delivered	1400lm (4000K)	
Lm/W	113lm/W (4000K)	
Beam Angle	75	
CRI	80	
ССТ	3000/4000/6500K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	6	
UGR	26	
Cut-Out Size	100mm	
Product Weight without Packaging	0.22 kg	

www.ansell-lighting.com

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 100,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	118 mm
Height	68 mm

