





@ansell_lighting





in Ansell Lighting



Vantage

Vantage CCT 3 Downlight DALI Code: AVANTLED3/DD3



applications









- One product provides 3000K,4000K and 6500K colour temperature options
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

Downlights	
Ancillary, Commercial, Education, Healthcare,	
Hospitality, Retail	
Performance	





- CCT selectable LED performance downlight suitable for commercial and education • Deep cut-off angle for glare control and comfort
 - Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
 - · Powered by Tridonic

GENERAL INFORMATION		
Wattage	20W	
Lumens Delivered	2100lm (4000K)	
Lm/W	112lm/W (4000K)	
Beam Angle	75	
CRI	80	
ССТ	3000/4000/6500K	
Input	220-240V	
Operating Temp	-25°C - 40°C	
SDCM	6	
UGR	25	
Cut-Out Size	150mm	
Product Weight without Packaging	0.53 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	172 mm	
Height	98 mm	