



@ansell_lighting



ansellighting



Ansell Lighting






ansell_lighting

Vantage

Vantage CCT 4 Downlight DALI

Code: AVANTLED4/DD3

| | |
|---------------|---|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Healthcare, Hospitality, Retail |
| Specification | Performance |



- CCT selectable LED performance downlight suitable for commercial and education applications
- One product provides 3000K, 4000K and 6500K colour temperature options
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm, 100mm, 150mm and 200mm
- Powered by Tridonic

| GENERAL INFORMATION | |
|----------------------------------|-----------------|
| Wattage | 27W |
| Lumens Delivered | 3200lm (4000K) |
| Lm/W | 121lm/W (4000K) |
| Beam Angle | 75 |
| CRI | 80 |
| CCT | 3000/4000/6500K |
| Input | 220-240V |
| Operating Temp | -25°C - 40°C |
| SDCM | 6 |
| UGR | 24 |
| Cut-Out Size | 200mm |
| Product Weight without Packaging | 0.64 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|--------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 100,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 230 mm |
| Height | 128 mm |

