











Vantage UGR<19


Vantage UGR<19 1 Cool White Downlight OCTO Code: AVANTLG1/CW/OCTO/M3

| Category | Downlights |
|---------------|---|
| Application | Ancillary, Commercial, Education, Healthcare, |
| | Hospitality, Retail |
| Specification | Performance |
| | |





Warrington: +44 (0) 1942 433333





PRODUCT FEATURES

- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

| GENERAL INFORMATION | | | |
|---------------------------------|------------|--|--|
| Wattage | 9W | | |
| Lumens Delivered | 800lm | | |
| Lm/W | 89lm/W | | |
| Beam Angle | 40 | | |
| CRI | 90 | | |
| CCT | 4000K | | |
| Input | 220-240V | | |
| Operating Temp | 0°C - 40°C | | |
| SDCM | 6 | | |
| UGR | 19 | | |
| Cut-Out Size | 68mm | | |
| Product Weight without Packagir | g 0.69 kg | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP20 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L80 72,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 82 mm | |
| Height | 54 mm | |