












## Vantage UGR<19


Vantage UGR<19 3 Cool White Downlight 1-10V Code: AVANTLG3/CW/DD4/M3

Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Retail
Specification	Performance









- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

GENERAL INFORMATION		
Wattage	28W	
Lumens Delivered	2800lm	
Lm/W	100lm/W	
Beam Angle	40	
CRI	90	
CCT	4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	6	
UGR	10	
Cut-Out Size	150mm	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP20		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L80 72,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	172 mm		
Height	98 mm		