



Category	Downlights	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Retail	
Specification	Performance	

Vantage UGR<19

Vantage UGR<19 3 Cool White Downlight Code: AVANTLG3/CW





PRODUCT FEATURES

Deep cut-off angle for glare control and comfort

150mm and 200mm

· Powered by Tridonic

- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- · Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

	GENERAL INFORMATION
Wattage	28W
Lumens Delivered	2800lm
Lm/W	100lm/W
Beam Angle	40
CRI	80
ССТ	4000K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	10
Cut-Out Size	150mm
Product Weight without Packagi	ng 0.316 kg

TECHNIC	AL INFORMATION
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 72,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	172 mm
Height	98 mm

· Downlight design allows installation into existing hole cut-outs from 68mm,100mm,





ansell_lighting





Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Retail
Specification	Performance

Vantage UGR<19

Vantage UGR<19 3 Cool White Downlight Code: AVANTLG3/CW









