



# Vantage Downlight

Part of the Downlights product category



**Model** Vantage UGR<19 3 Cool White Downlight  
**Code** AVANTLG3/CW  
**Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

## GENERAL INFORMATION

Input	220-240V
Wattage	28W
Operating Temp	-20°C - 40°C
Lumens Delivered	2800lm
lm/W	100lm/W
CCT	4000K
UGR	10
Beam Angle	40

## MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without	0.316 kg
Packaging	
Colour / Finish	White
Diameter	172 mm
Height	98 mm

## TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.9
L70 @ 25°C	L70 B50 78,000h

## PRODUCT FEATURES

- UGR<19 performance downlight suitable for commercial and education applications
- Deep cut-off angle for glare control and comfort
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Downlight design allows installation into existing hole cut-outs from 68mm, 100mm, 150mm and 200mm
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities





# Vantage Downlight



Part of the Downlights product category

- Model** Vantage UGR<19 3 Cool White Downlight
- Code** AVANTLG3/CW
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

