














Vantage UGR<19


Vantage UGR<19 3 Warm White Downlight DALI Code: AVANTLG3/WW/DD3

Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Retail
Specification	Performance









- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

GENERAL INFORMATION		
Wattage	28W	
Lumens Delivered	2600lm	
Lm/W	93lm/W	
Beam Angle	40	
CRI	90	
CCT	3000K	
Input	220-240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
UGR	10	
Cut-Out Size	150mm	
Product Weight without Packaging	0.316 kg	

www.ansell-lighting.com

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 72,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	172 mm	
Height	98 mm	