





# Vantage UGR<19

Vantage UGR<19 4 Cool White Downlight Switch  
Code: AVANTLG4/CW/DD1/SM3

|               |   |
|---------------|---|
| Category      | Downlights  |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Retail |
| Specification | Performance   |



## PRODUCT FEATURES

- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm, 100mm, 150mm and 200mm
- Powered by Tridonic

| GENERAL INFORMATION |            |
|---------------------|------------|
| Wattage             | 36W        |
| Lumens Delivered    | 3900lm     |
| Lm/W                | 108lm/W    |
| Beam Angle          | 40         |
| CRI                 | 90         |
| CCT                 | 4000K      |
| Input               | 220/240V   |
| Operating Temp      | 0°C - 40°C |
| SDCM                | 6          |
| UGR                 | 14         |
| Cut-Out Size        | 200mm      |

| TECHNICAL INFORMATION          |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | White       |
| IP Rating                      | IP20        |
| Class Protection               | 2           |
| Internal / External            | Internal    |
| Surface / Recessed / Suspended | Recessed    |
| Lumen Depreciation             | L80 72,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Diameter                       | 230 mm      |
| Height                         | 128 mm      |

