



Vantage UGR<19


Vantage UGR<19 4 Warm White Downlight Switch Code: AVANTLG4/WW/DD1






- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

| Category | Downlights | |
|---------------|---|--|
| Application | Ancillary, Commercial, Education, Healthcare, | |
| | Hospitality, Retail | |
| Specification | Performance | |





- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm,
 150mm and 200mm
- Powered by Tridonic

| GENERAL INFORMATION | | |
|----------------------------------|--------------|--|
| Wattage | 36W | |
| Lumens Delivered | 3800lm | |
| Lm/W | 106lm/W | |
| Beam Angle | 40 | |
| CRI | 90 | |
| CCT | 3000K | |
| Input | 220-240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 6 | |
| UGR | 14 | |
| Cut-Out Size | 200mm | |
| Product Weight without Packaging | 0.538 kg | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP20 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L80 72,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 230 mm | |
| Height | 128 mm | |
| | | |