





Downlights

Hospitality, Retail

Performance








Vantage UGR<19

Vantage UGR<19 4 Warm White Downlight 1-10V Code: AVANTLG4/WW/DD4

| | 1 | | |
|--|-----|----------------|--|
| | | | |
| | | | |
| | , [| H ₁ | |
| | | | |
| | | V | |






Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort

AVANTLG4

- Downlight design allows installation into existing hole cut-outs from 68mm,100mm, 150mm and 200mm
- · Powered by Tridonic

| GENERAL INFORMATION | | | |
|---------------------|--------------|--|--|
| Wattage | 36W | | |
| Lumens Delivered | 3800lm | | |
| Lm/W | 106lm/W | | |
| Beam Angle | 40 | | |
| CRI | 90 | | |
| CCT | 3000K | | |
| Input | 220-240V | | |
| Operating Temp | -20°C - 40°C | | |
| SDCM | 6 | | |
| UGR | 14 | | |
| Cut-Out Size | 200mm | | |
| | | | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|-------------|--|--|
| Light Source | LED | | |
| Colour / Finish | White | | |
| IP Rating | IP20 | | |
| Class Protection | 2 | | |
| Internal / External | Internal | | |
| Surface / Recessed / Suspended | Recessed | | |
| Lumen Depreciation | L80 72,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Diameter | 230 mm | | |
| Height | 128 mm | | |