



Vantage UGR<19

Vantage UGR<19 4 Warm White Downlight Code: AVANTLG4/WW/M3

Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Retail
Specification	Performance



- **PRODUCT FEATURES**
- UGR<19 performance downlight suitable for commercial and education applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Deep cut-off angle for glare control and comfort
- Downlight design allows installation into existing hole cut-outs from 68mm,100mm,
 150mm and 200mm
- Powered by Tridonic

GENERAL INFORMATION			
Wattage	36W		
Lumens Delivered	3800lm		
Lm/W	106lm/W		
Beam Angle	40		
CRI	90		
ССТ	3000K		
Input	220-240V		
Operating Temp	0°C - 40°C		
SDCM	6		
UGR	14		
Cut-Out Size	200mm		
Product Weight without Packaging	0.538 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 72,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	230 mm	
Height	128 mm	