



Bulkheads

Performance

@ansell_lighting





in Ansell Lighting



Vision

Vision CCT Dual Wattage Switch Dim White Code: AVIL/1/W/DD1






Category

Application

Specification



Ancillary, Hospitality, Outdoor, Residential, Retail

PRODUCT FEATURES

- IP65 CCT polycarbonate luminaire suitable for healthcare, educational, commercial and industrial applications
- UV stabilised polycarbonate constructions allows installation into areas exposed to adverse weather conditions
- · Clip in gear tray ensures quick installation
- Dimmable, Photocell, MWS and Emergency options available

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Top, bottom and side conduit entry covers retain sleek appearance when not in use
- Corridor function options available for effective reduction in energy consumption
- · Powered by Tridonic

GENERAL INFORMATION		
Wattage	18W	
Lumens Delivered	1300lm - 2100lm	
Lm/W	130lm/W - 120lm/W	
Beam Angle	110	
CRI	80	
ССТ	3000/4000K	
Input	220-240V	
Operating Temp	5°C - 40°C	
SDCM	3	
Energy efficiency class	С	
Product Weight without Packaging	1.954 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	350 mm	
Height	110 mm	