












Volo

Volo CCT Dual Wattage Recessed Modular DALI Code: AVOLO/DD3/M3

Category	Commercial Panels	
Application	Ancillary, Commercial, Education, Healthcare, Retail	
Specification	Architectural	



- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- Can be surface and suspended, suspension kit supplied separately
- Selectable CCT between 3000K and 4000K
- Integral PIR option discreetly positioned in the end cap

- High performance indirect recessed luminaire
- Dual direct/indirect output. Direct from the centre micro-prism central diffuser coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- OCTO tunable white option (3000K-6500K)
- High performance optics provide high efficiency while still offering optimum glare control and comfort for task/office applications

GENERAL INFORMATION		
Wattage	34W	
Lumens Delivered	2700lm - 4200lm (4000K)	
Lm/W	128lm/W - 124lm/W (4000K)	
Beam Angle	85	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	0°C - 50°C	
SDCM	3	
UGR	17	
Cut-Out Size	580x580mm	
Product Weight without Packaging	6.353 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP40	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Recessed, Suspended	
Lumen Depreciation	L80 82,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	80 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

