



# Inground Uplight

Part of the Feature Lighting product category



<b>Model</b>	GU10 Adjustable Inground Uplight
<b>Code</b>	AWO/GU10
<b>Application</b>	Outdoor, Residential

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	35W
<b>Operating Temp</b>	-10°C - 25°C

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium
<b>Diffuser Material</b>	Glass
<b>Product Weight without</b>	1.01 kg
<b>Packaging</b>	
<b>Colour / Finish</b>	Stainless Steel
<b>Diameter</b>	149 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	GU10
<b>Internal / External</b>	External
<b>Surface / Recessed / Suspended</b>	Recessed

## PRODUCT FEATURES

- GU10 adjustable inground uplight suitable for residential applications
- Die-cast aluminium housing with a clear toughened glass diffuser of 8mm thickness
- 304 stainless steel top ring and stainless steel allen key screws
- Adjustable lampholder to allow up to 15° vertical inclination of lamp
- Suitable for pedestrian traffic with a static impact resistance of up to 1000kgs





# Inground Uplight

Part of the Feature Lighting product category



<b>Model</b>	GU10 Adjustable Inground Uplight
<b>Code</b>	AWO/GU10
<b>Application</b>	Outdoor, Residential

