



GU10 Adjustable Inground Uplight Stainless Steel



- GU10 adjustable inground uplight suitable for residential applications
- Die-cast aluminium housing with a clear toughened glass diffuser of 8mm thickness
- 304 stainless steel top ring and stainless steel allen key screws
- Adjustable lampholder to allow up to 15° vertical inclination of lamp
- Suitable for pedestrian traffic with a static impact resistance of up to 1000kgs
- Option to add OCTO Connected by WiZ smart GU10 lamp
- Caution: surface glass temperature will get very hot under normal halogen operation. It is recommended to use GU10 LED lamps for cooler operation.

Features

Feature 1	GU10 adjustable inground uplight suitable for residential applications
Feature 2	Die-cast aluminium housing with a clear toughened glass diffuser of 8mm thickness
Feature 3	304 stainless steel top ring and stainless steel allen key screws
Feature 4	Adjustable lampholder to allow up to 15° vertical inclination of lamp
Feature 5	Suitable for pedestrian traffic with a static impact resistance of up to 1000kgs
Feature 6	Option to add OCTO Connected by WiZ smart GU10 lamp



Feature 7

Caution: surface glass temperature will get very hot under normal halogen operation. It is recommended to use GU10 LED lamps for cooler operation.

General Information

Lamp Type	GU10
IP Rating	IP65
IK Rating	IK10
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
OCTO Category	OCTO compatible WiZ Connected
Warranty (Years)	3
Material	Aluminium, Stainless Steel

Technical Information

Wattage	50W
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C - 25°C



