





Wolf

Wolf CCT Multi Wattage Wallpack Microwave
Code: AWOLF/BLK/MWS/M3

| | |
|---------------|---|
| Category | Bulkheads |
| Application | Ancillary, Commercial, Healthcare, Hospitality, Industrial, Outdoor, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations, helps with compliance with Dark Skies recommendations
- High efficiency up to 120 Lm/W
- Multiple conduit entry and BESA fixing points
- Advanced lens technology offers wide distribution for optimum spacing and uniformity; whilst ensuring minimal uplight and light pollution
- Power selectable; offering a choice of 3 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- 20mm East and West side entry for surface conduit and through-wire

| GENERAL INFORMATION | |
|----------------------------------|----------------------------------|
| Wattage | 19W / 21W / 30W |
| Lumens Delivered | 2200lm / 2400lm / 3600lm (4000K) |
| Lm/W | 120lm/W (4000K) |
| Beam Angle | 70/140 |
| CRI | 82 |
| CCT | 3000/4000K |
| Input | 220-240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 3 |
| Product Weight without Packaging | 3.278 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Pole, Wall |
| Lumen Depreciation | L80 84,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 220 mm |

