




Wolf Mini

Wolf Mini Wallpack CCT Switch Dim DALI-Code: AWOLF/MINI/SG/DD1/DM3








Category

Application

Specification



Ancillary, Commercial, Healthcare, Hospitality,

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations
- · High efficiency up to 125 Lm/W
- Multiple conduit, 20mm East and West side entries and rear BESA mounting
- Advanced lens technology offers wide distribution for optimum spacing and uniformity;
 whilst ensuring minimal uplight and light pollution

Bulkheads

Performance

Industrial, Outdoor, Retail

- · Power selectable; offering a choice of 2 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- Dimmable and Smart options available

GENERAL INFORMATION		
Wattage	9W	
Lumens Delivered	500lm / 1000lm (4000K)	
Lm/W	125lm/W (4000K)	
Beam Angle	70/140	
CRI	82	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Wall	
Lumen Depreciation	L80 84,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	155 mm	

