





Wolf Mini

Wolf Mini Wallpack CCT Switch Dim DALI-
Code: AWOLF/MINI/SG/DD1/DM3

| | |
|---------------|---|
| Category | Bulkheads |
| Application | Ancillary, Commercial, Healthcare, Hospitality, Industrial, Outdoor, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations
- High efficiency up to 125 Lm/W
- Multiple conduit, 20mm East and West side entries and rear BESA mounting
- Advanced lens technology offers wide distribution for optimum spacing and uniformity; whilst ensuring minimal uplight and light pollution
- Power selectable; offering a choice of 2 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- Dimmable and Smart options available

| GENERAL INFORMATION | |
|---------------------|--------------------|
| Wattage | 4/8W |
| Lumens Delivered | 500/1000lm (4000K) |
| Lm/W | 125lm/W (4000K) |
| Beam Angle | 70/140 |
| CRI | 82 |
| CCT | 3000/4000K |
| Input | 220/240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 3 |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | Silver Grey |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Wall |
| Lumen Depreciation | L80 84,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 156 mm |

