




## Wolf Mini

Wolf Mini Wallpack CCT DALI DALI-Emergency Code: AWOLF/MINI/SG/DD3/DM3








Category

Application

Specification



Ancillary, Commercial, Healthcare, Hospitality,

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations
- · High efficiency up to 125 Lm/W
- Multiple conduit, 20mm East and West side entries and rear BESA mounting
- Advanced lens technology offers wide distribution for optimum spacing and uniformity;
  whilst ensuring minimal uplight and light pollution

Bulkheads

Performance

Industrial, Outdoor, Retail

- Power selectable; offering a choice of 2 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- Dimmable and Smart options available

GENERAL INFORMATION	
Wattage	8W
Lumens Delivered	500lm / 1000lm (4000K)
Lm/W	125lm/W (4000K)
Beam Angle	70/140
CRI	82
CCT	3000/4000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3

TECHNICAL INFORMATION	
LED	
Silver Grey	
IP65	
1	
External	
Wall	
L80 84,000h	
5	
Yes	
155 mm	

