





Bulkheads

Performance





Industrial, Outdoor, Retail




Wolf Mini

Wolf Mini Wallpack CCT Photocell Silver Gray Code: AWOLF/MINI/SG/PC








Category

Application

Specification



Ancillary, Commercial, Healthcare, Hospitality,

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations
- · High efficiency up to 125 Lm/W
- Multiple conduit, 20mm East and West side entries and rear BESA mounting
- Advanced lens technology offers wide distribution for optimum spacing and uniformity;
 whilst ensuring minimal uplight and light pollution
- Power selectable; offering a choice of 2 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- Dimmable and Smart options available

| GENERAL INFORMATION | | |
|----------------------------------|------------------------|--|
| Wattage | 4.5W/9W | |
| Lumens Delivered | 500lm / 1000lm (4000K) | |
| Lm/W | 125lm/W (4000K) | |
| Beam Angle | 70/140 | |
| CRI | 82 | |
| CCT | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 3 | |
| Product Weight without Packaging | 1.85 kg | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | Silver Grey | |
| IP Rating | IP65 | |
| Class Protection | 1 | |
| Internal / External | External | |
| Surface / Recessed / Suspended | Wall | |
| Lumen Depreciation | L80 84,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Height | 155 mm | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750