




Wolf


Wolf CCT Multi Wattage Wallpack Switch Dim Code: AWOLF/SG/DD1/SM3



- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations, helps with compliance with Dark Skies recommendations
- · High efficiency up to 120 Lm/W
- Multiple conduit entry and BESA fixing points

Category	Bulkheads
Application	Ancillary, Commercial, Healthcare, Hospitality,
	Industrial, Outdoor, Retail
Specification	Performance





- Advanced lens technology offers wide distribution for optimum spacing and uniformity;
 whilst ensuring minimal uplight and light pollution
- · Power selectable; offering a choice of 3 outputs, in one luminaire
- · Electrostatic paint finish for enhanced corrosion resistance
- · 20mm East and West side entry for surface conduit and through-wire

GENERAL INFORMATION		
Wattage	30W	
Lumens Delivered	2200lm / 2400lm / 3600lm (4000K)	
Lm/W	120lm/W (4000K)	
Beam Angle	70/140	
CRI	82	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Pole, Wall	
Lumen Depreciation	L80 84,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	220 mm	