









Bulkheads

Performance

Industrial, Outdoor, Retail




Wolf

Wolf CCT Multi Wattage Wallpack OCTO Smart Code: AWOLF/SG/OCTO/SM3







Category

Application

Specification



Ancillary, Commercial, Healthcare, Hospitality,

PRODUCT FEATURES

- Modern, robust die-cast aluminium low glare wall pack suitable for commercial and industrial applications
- Reduced light pollution with 0% upward light distribution, helps with compliance with Dark Skies recommendations, helps with compliance with Dark Skies recommendations
- High efficiency up to 120 Lm/W

www.ansell-lighting.com

Multiple conduit entry and BESA fixing points

- Advanced lens technology offers wide distribution for optimum spacing and uniformity;
 whilst ensuring minimal uplight and light pollution
- Power selectable; offering a choice of 3 outputs, in one luminaire
- Electrostatic paint finish for enhanced corrosion resistance
- 20mm East and West side entry for surface conduit and through-wire

| GENERAL INFORMATION | | |
|---------------------|----------------------------------|--|
| Wattage | 30W | |
| Lumens Delivered | 2200lm / 2400lm / 3600lm (4000K) | |
| Lm/W | 120lm/W (4000K) | |
| Beam Angle | 70/140 | |
| CRI | 82 | |
| CCT | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 40°C | |
| SDCM | 3 | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | Silver Grey | |
| IP Rating | IP65 | |
| Class Protection | 1 | |
| Internal / External | External | |
| Surface / Recessed / Suspended | Pole, Wall | |
| Lumen Depreciation | L80 84,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Height | 220 mm | |