



# Z LED Eco

Part of the High/Low Bay product category



**Model** Z LED ECO Highbay 2 CCT  
**Code** AZLE2/2  
**Application** Ancillary, Hospitality, Industrial, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	150/175/200W
<b>Operating Temp</b>	-45°C - 45°C
<b>Lumens Delivered</b>	19,500/22,750/26,000lm (4000K)
<b>lm/W</b>	130lm/W
<b>CCT</b>	4000K / 5000K / 6500K
<b>UGR</b>	28
<b>Beam Angle</b>	90

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	2.04 kg
<b>Colour / Finish</b>	Black
<b>Diameter</b>	354 mm
<b>Height</b>	89 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Suspended
<b>Power Factor</b>	0.9
<b>L70 @ 25°C</b>	L70 B50 60,000h

## PRODUCT FEATURES

- Sleek and robust LED low/high bay for industrial applications and ancillary areas
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- 3 x Power (130lm/W) and CCT selectable between 4000K, 5000K and 6500K
- Lensed diffuser design helps to control the beam angle, offering better light distribution
- High efficiency up to 130lm/w





# Z LED Eco



Part of the High/Low Bay product category

**Model** Z LED ECO Highbay 2 CCT  
**Code** AZLE2/2  
**Application** Ancillary, Hospitality, Industrial, Retail

