Z LED Eco

5YR IP66 IK09 ON-SITE WARRANTY 2 YEARS

Part of the High/Low Bay product category

Model	Z LED ECO Highbay 2 CCT
Code	AZLE2/2
Application	Ancillary, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	150/175/200W
Operating Temp	-45°C - 45°C
Lumens Delivered	19,500/22,750/26,000lm (4000K)
lm/W	130lm/W
CCT	4000K / 5000K / 6500K
UGR	28
Beam Angle	90

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.04 kg
Colour / Finish	Black
Diameter	354 mm
Height	89 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Sleek and robust LED low/high bay for industrial applications and ancillary areas
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- 3 x Power (130lm/W) and CCT selectable between 4000K, 5000K and 6500K
- Lensed diffuser design helps to control the beam angle, offering better light distribution
- High efficiency up to 130lm/w





Z LED Eco

5YR IP66 IK09 ON-SITE WARRANTY 2 YEARS

Part of the High/Low Bay product category

Model	Z LED ECO Highbay 2 CCT
Code	AZLE2/2
Application	Ancillary, Hospitality, Industrial, Retail













