Z LED Eco

3YR IP66 IK09 ON-SITE WARRANTY 2 YEARS

Part of the High/Low Bay product category

Model	Z LED ECO Highbay 3 Cool White
Code	AZLE3/1/CW
Application	Ancillary, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	200W
Operating Temp	-45°C - 45°C
Lumens Delivered	23500lm
lm/W	120lm/W
CCT	4000K
UGR	28
Beam Angle	90

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.87 kg
Colour / Finish	Black
Diameter	354 mm
Height	87 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Suspended
Power Factor	0.95
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Sleek and robust LED low/high bay for industrial applications and ancillary areas
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Lensed diffuser design helps to control the beam angle, offering better light distribution
- High efficiency up to 120lm/w
- Integral on-board driver reduces the overall size and weight of product, resulting in a slim, lightweight and easy to install unit





Z LED Eco

Part of the High/Low Bay product category

Model	Z LED ECO Highbay 3 Cool White
Code	AZLE3/1/CW
Application	Ancillary, Hospitality, Industrial, Retail









