

Z LED PLUS


Z LED PLUS 75W Daylight DALI Code: AZLEDPLUS/1/DL/DD3




- Industry leading super high efficiency (200 Im/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation



Category	High/Low Bay	
Application	Ancillary, Hospitality, Industrial, Retail	
Specification	Performance	





- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- · Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

	GENERAL INFORMATION
Wattage	75W
Lumens Delivered	15000lm
Lm/W	2001m/W
Beam Angle	110
CRI	70
CCT	4000K
Input	220-240V
Operating Temp	-35°C - 50°C
SDCM	4
Product Weight without Packagi	ng 2.16 kg

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	Black			
IP Rating	IP65			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L80 100,000h			
Warranty (Years)	6			
CE Mark	Yes			
Diameter	265 mm			
Height	152 mm			